

PRODUCT-DETAILS

4125C6W B11

4125C6W B11 Industrial Connector



General Information

Extended Product Type	4125C6W B11
Product ID	2CMA192674R1000
EAN	7392696926744
Catalog Description	4125C6W B11 Industrial Connector
Long Description	Connector, earthing sleeve position 6h, rated current 125A, IP67 watertight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red, Multipack 11 pcs

Ordering

E-Number (Sweden)	19608710
EAN	7392696926744
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	11 piece

Dimensions

Product Net Width	119 mm
Product Net Height	123 mm
Product Net Weight	1.53 kg
Mechanical Drawings	9AKK107492A4189

Container Information

Package Level 1 Width	383 mm
Package Level 1 Depth / Length	383 mm
Package Level 1 Height	383 mm
Package Level 1 Gross Weight	16.83 kg
Package Level 1 EAN	7392696926751
Package Level 1 Units	box 11 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	2241.56 kg
Package Level 2 EAN	7392696078856
Package Level 2 Units	pallet (lift) 132 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	16 ... 50 mm ²
Cable Diameter	24 ... 48 mm
Cable Entry Position	Anti-kink sleeve
Color	Red
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Connector
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#4125C6W B11
Number of Poles	5
Order Multiple	11 piece
Product Main Type	TC
Product Name	Industrial Connector
Protection Type	Watertight
Rated Current (I _N)	125 A
Rated Voltage (U _r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product	IEC Industrial Plugs and Sockets

Class	
Instructions and Manuals	2CMC000038M0001
Installation Manual	2CMC000038M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440509
UNSPSC	39120000

Technical

Wire Size	3 ... 1 AWG
Tightening Torque	WireClamp5.6 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Connectors

