

PRODUCT-DETAILS

416RAM6 B75

Socket-outlet, panel mounting, 6h, 16A, IP44, minimized flange, angled, 3P+N+E, 75pcs



General Information

Extended Product Type	416RAM6 B75
Product ID	2CMA192704R1000
EAN	7392696927048
Catalog Description	Socket-outlet, panel mounting, 6h, 16A, IP44, minimized flange, angled, 3P+N+E, 75pcs
Long Description	Socket Outlet Panel Mounting, earthing sleeve position 6h, rated current 16A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

Ordering

E-Number (Sweden)	19609630
EAN	7392696927048
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	75 piece

Dimensions

Product Net Width	94 mm
Product Net Height	99 mm
Product Net Weight	0.24 kg

Container Information

Package Level 1 Width	383 mm
Package Level 1 Depth / Length	383 mm
Package Level 1 Height	383 mm
Package Level 1 Gross Weight	18 kg
Package Level 1 EAN	7392696927253
Package Level 1 Units	box 75 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	16220 kg
Package Level 2 EAN	7392696078979
Package Level 2 Units	pallet (lift) 900 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	2CHC660153X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614201
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Cable Diameter	13 ... 17 mm
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Socket outlet for panel mounting
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#416RAM6 "B75"
Mounting Holes	66x66
Mounting Type	minimized flange, angled

Number of Poles	5
Order Multiple	75 piece
Product Main Type	ERAM
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current (I_n)	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440504
UNSPSC	39120000

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

