

PRODUCT-DETAILS

416BS6 B60

Surface inlet, 6h, 16A, IP44, 3P+N+E, 60pcs



General Information

Extended Product Type	416BS6 B60
Product ID	2CMA192722R1000
EAN	7392696927222
Catalog Description	Surface inlet, 6h, 16A, IP44, 3P+N+E, 60pcs
Long Description	Surface Inlet, earthing sleeve position 6h, rated current 16A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Grey

Ordering

E-Number (Sweden)	19633330
EAN	7392696927222
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	60 piece

Dimensions

Product Net Width	79 mm
Product Net Height	100 mm
Product Net Weight	0.2 kg
Mechanical Drawings	9AKK107680A3016

Container Information

Package Level 1 Width	383 mm
Package Level 1 Depth / Length	383 mm
Package Level 1 Height	383 mm
Package Level 1 Gross Weight	12 kg
Package Level 1 EAN	7392696927239
Package Level 1 Units	box 60 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	8660 kg
Package Level 2 EAN	7392696079280
Package Level 2 Units	pallet (lift) 720 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	2CHC660161X0201
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Cable Diameter	18 mm
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Surface Inlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#416BS6 "B60"
Mounting Holes	91x67

Number of Poles	5
Order Multiple	60 piece
Product Main Type	EBS
Product Name	Wall mounted inlet
Protection Type	Splashproof
Rated Current (I_n)	16 A
Rated Frequency (f)	50 ... 60 Hz
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Surface Inlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440519
UNSPSC	39120000

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Inlets

