


PRODUCT-DETAILS

463BS6 "B15"

Surface inlet, 6h, 63A, IP44, 3P+N+E, 15pcs



General Information

Extended Product Type	463BS6 "B15"
Product ID	2CMA192726R1000
EAN	7392696927260
Catalog Description	Surface inlet, 6h, 63A, IP44, 3P+N+E, 15pcs
Long Description	Surface Inlet, earthing sleeve position 6h, rated current 63A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

Ordering

E-Number (Sweden)	19634210
EAN	7392696927260
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	15 piece

Dimensions

Product Net Width	107 mm
Product Net Height	117 mm
Product Net Weight	0.9 kg

Container Information

Package Level 1 Width	381 mm
Package Level 1 Depth / Length	381 mm
Package Level 1 Height	381 mm
Package Level 1 Gross Weight	13.5 kg
Package Level 1 EAN	7392696927277
Package Level 1 Units	box 15 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	2450 kg
Package Level 2 EAN	7392696079297
Package Level 2 Units	pallet (lift) 180 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	2CHC660163X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1519130
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm²
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Surface Inlet
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#463BS6 "B15"
Mounting Holes	170x95
Number of Poles	5

Order Multiple	15 piece
Product Main Type	TBS
Product Name	Wall mounted inlet
Protection Type	Splashproof
Rated Current (I_n)	63 A
Rated Frequency (f)	50 ... 60 Hz
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Surface Inlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000040M0001
Installation Manual	2CMC000040M0001
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440519
UNSPSC	39120000

Technical

Wire Size	8 ... 4 AWG
Tightening Torque	WireClamp3.5 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Inlets

