

PRODUCT-DETAILS

216RU12

Industrial socket outlets for panel mounting,
2P+E, 16 A, Isol. Transformer V



General Information

Extended Product Type	216RU12
Product ID	2CMA193172R1000
EAN	7392696931724
Catalog Description	Industrial socket outlets for panel mounting, 2P+E, 16 A, Isol. Transformer V
Long Description	Panel mounted socket, earthing sleeve position 12h, rated current 16A, IP44 splashproof, unified flange, straight, 2-poles+earth, frequency 50-60 Hz, color code Grey

Ordering

E-Number (Sweden)	E2416622
E-Number (Finland)	2416622
E-Number (Norway)	2416622
EAN	7392696931724
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	75 mm
Product Net Height	79 mm
Product Net Weight	0.200 kg

Container Information

Package Level 1 Width	138 mm
Package Level 1 Depth / Length	158 mm
Package Level 1 Height	345 mm
Package Level 1 Gross Weight	2 kg
Package Level 1 EAN	7392696661720
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	1340 kg
Package Level 2 EAN	7392696079402
Package Level 2 Units	pallet (lift) 660 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm ²
Cable Diameter	6 ... 13 mm
Color	Grey
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Panel mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#216RU12
Mounting Holes	60-61x60-61
Mounting Type	Unified straight flange
Number of Poles	3
Order Multiple	10 piece
Product Main Type	ERU
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current (I _n)	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U _r)	Isol. Transformer V

Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440504
UNSPSC	39121406

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

