

## PRODUCT-DETAILS

# 216B6

Inlet, panel mounting, 6h, 16A, IP44, minimized flange, straight, 2P+E



## General Information

|                       |                                                                                                                                                                       |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 216B6                                                                                                                                                                 |
| Product ID            | 2CMA193338R1000                                                                                                                                                       |
| EAN                   | 7392696933384                                                                                                                                                         |
| Catalog Description   | Inlet, panel mounting, 6h, 16A, IP44, minimized flange, straight, 2P+E                                                                                                |
| Long Description      | Panel mounted inlet, minimized flange, straight, earthing sleeve position 6h, rated current 16A, IP44 splashproof, 2-poles+earth, frequency 50-60 Hz, color code Blue |

## Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2417331            |
| E-Number (Finland)     | 2421532             |
| E-Number (Norway)      | 1544002             |
| EAN                    | 7392696933384       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 10 piece            |

## Dimensions

|                    |       |
|--------------------|-------|
| Product Net Width  | 56 mm |
| Product Net Height | 60 mm |

|                    |        |
|--------------------|--------|
| Product Net Weight | 0.1 kg |
|--------------------|--------|

## Container Information

|                                |                          |
|--------------------------------|--------------------------|
| Package Level 1 Width          | 120 mm                   |
| Package Level 1 Depth / Length | 138 mm                   |
| Package Level 1 Height         | 285 mm                   |
| Package Level 1 Gross Weight   | 1 kg                     |
| Package Level 1 EAN            | 7392696663380            |
| Package Level 1 Units          | box 10 piece             |
| Package Level 2 Width          | 800 mm                   |
| Package Level 2 Depth / Length | 1200 mm                  |
| Package Level 2 Height         | 900 mm                   |
| Package Level 2 Gross Weight   | 1220 kg                  |
| Package Level 2 EAN            | 7392696080545            |
| Package Level 2 Units          | pallet (lift) 1200 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 2CHC660161X0201 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                           |
|------------------------|---------------------------|
| Additional Information | 2P+E                      |
| Ambient Temperature    | -25 ... 40 °C             |
| Cable Cross-Section    | 1.5 ... 4 mm <sup>2</sup> |
| Cable Diameter         | 6 ... 13 mm               |
| Color                  | Blue                      |
| Connection Type        | Screw                     |
| Degree of Protection   | IP44                      |
| Design                 | Surface mounted plug      |
| Frequency (f)          | 50 Hz<br>60 Hz            |
| Function               | Panel mounted inlet       |
| Housing Material       | Plastic (PA)              |

|                            |                                  |
|----------------------------|----------------------------------|
| Invoice Description        | Ind. P&S#216B6                   |
| Mounting Holes             | 45x45                            |
| Mounting Type              | Minimized straight flange        |
| Number of Poles            | 3                                |
| Order Multiple             | 10 piece                         |
| Product Main Type          | EB                               |
| Product Name               | Panel mounted inlet              |
| Protection Type            | Splashproof                      |
| Rated Current ( $I_n$ )    | 16 A                             |
| Rated Frequency (f)        | 50 ... 60 Hz                     |
| Rated Voltage ( $U_r$ )    | 200 ... 250 V                    |
| Recommended Screw Driver   | PH2                              |
| Standards                  | IEC 60309-1, -2                  |
| Suitable For               | Inlets for Panel Mounting        |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC700014C0016                  |
| RAL Number                 | RAL 7001 - Silver Grey           |

Classifications

|        |          |
|--------|----------|
| eClass | 27440519 |
| UNSPSC | 39121406 |

Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 14 ... 12 AWG    |
| Tightening Torque | WireClamp0.8 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Inlets for Panel Mounting

