


## PRODUCT-DETAILS

# 216B1

Inlet Panel Mounting, minimized flange, straight, earthing sleeve position 1h, rated current 16A, IP44 splashproof, 2-poles+earth, frequency ACz, color code Grey



## General Information

|                       |                                                                                                                                                                                                                             |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 216B1                                                                                                                                                                                                                       |
| Product ID            | 2CMA193341R1000                                                                                                                                                                                                             |
| EAN                   | 7392696933414                                                                                                                                                                                                               |
| Catalog Description   | Inlet Panel Mounting, minimized flange, straight, earthing sleeve position 1h, rated current 16A, IP44 splashproof, 2-poles+earth, frequency ACz, color code Grey                                                           |
| Long Description      | Panel mounted inlet, minimized flange, straight, earthing sleeve position 1h, rated current 16A, IP44 splashproof, 2-poles+earth, frequency ACz, color code Grey Clock Position Of Grounding Contact 1 hour Color code Grey |

## Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | 2417332             |
| E-Number (Finland)     | 2417332             |
| E-Number (Norway)      | 2417332             |
| EAN                    | 7392696933414       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 10 piece            |

## Dimensions

|                    |          |
|--------------------|----------|
| Product Net Width  | 56 mm    |
| Product Net Height | 60 mm    |
| Product Net Weight | 0.100 kg |

## Container Information

|                                |                          |
|--------------------------------|--------------------------|
| Package Level 1 Width          | 120 mm                   |
| Package Level 1 Depth / Length | 138 mm                   |
| Package Level 1 Height         | 285 mm                   |
| Package Level 1 Gross Weight   | 1 kg                     |
| Package Level 1 EAN            | 7392696663410            |
| Package Level 1 Units          | box 10 piece             |
| Package Level 2 Width          | 800 mm                   |
| Package Level 2 Depth / Length | 1200 mm                  |
| Package Level 2 Height         | 900 mm                   |
| Package Level 2 Gross Weight   | 1220 kg                  |
| Package Level 2 EAN            | 7392696080552            |
| Package Level 2 Units          | pallet (lift) 1200 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 2CHC660161X0201 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                                 |                           |
|---------------------------------|---------------------------|
| Additional Information          | 2P+E                      |
| Ambient Temperature             | -25 ... 40 °C             |
| Cable Cross-Section             | 1.5 ... 4 mm <sup>2</sup> |
| Cable Diameter                  | 6 ... 13 mm               |
| Color                           | Grey                      |
| Connection Type                 | Screw                     |
| Degree of Protection            | IP44                      |
| Design                          | Surface mounted plug      |
| Frequency (f)                   | AC Hz                     |
| Function                        | Panel mounted inlet       |
| Housing Material                | Plastic (PA)              |
| Invoice Description             | Ind. P&S#216B1            |
| Mounting Holes                  | 45x45                     |
| Mounting Type                   | Minimized straight flange |
| Number of Poles                 | 3                         |
| Order Multiple                  | 10 piece                  |
| Product Main Type               | EB                        |
| Product Name                    | Panel mounted inlet       |
| Protection Type                 | Splashproof               |
| Rated Current (I <sub>N</sub> ) | 16 A                      |
| Rated Voltage (U <sub>r</sub> ) | Optional voltage V        |

|                            |                                  |
|----------------------------|----------------------------------|
| Recommended Screw Driver   | PH2                              |
| Standards                  | IEC 60309-1, -2                  |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC700014C0016                  |
| RAL Number                 | RAL 7001 - Silver Grey           |

**Classifications**

|        |          |
|--------|----------|
| eClass | 27440519 |
| UNSPSC | 39121406 |

**Technical**

|                   |                  |
|-------------------|------------------|
| Wire Size         | 14 ... 12 AWG    |
| Tightening Torque | WireClamp0.8 N·m |

**Categories**

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Inlets for Panel Mounting

