


PRODUCT-DETAILS

DDA203 A-25/0.03 AP-R 230V

DDA203 A-25/0.03 AP-R 230V Residual Current Device Block



General Information

Extended Product Type	DDA203 A-25/0.03 AP-R 230V
Product ID	2CSB203491R1250
EAN	8012542750338
Catalog Description	DDA203 A-25/0.03 AP-R 230V Residual Current Device Block
Long Description	The RCD block DDA200 series is suitable for assembly with MCBs S200 series. It assures protection against the effects of sinusoidal alternating and direct pulsating earth fault currents, providing the best compromise between safety and continuity in the service thanks to the resistance to unwanted trippings. Protection against indirect contacts and additional protection against direct (with sensitivity = 30 mA) contacts. Applications: residential, commercial, industrial.

Technical

Standards	EN 61009 Ann. G
Product Name	Residual Current Device Block
Type of Residual Current	A type
Rated Voltage (U_r)	230...400 V
Rated Operational Voltage	230/400 V
Rated Insulation Voltage (U_i)	500 V
Rated Impulse Withstand Voltage (U_{imp})	4 kV
Rated Current (I_n)	25 A
Rated Residual Current	30 mA

Maximum Surge Current	3 kA
Leakage Current Type	A
Rated Frequency (f)	50/60 Hz
Power Loss	at Rated Operating Conditions per Pole 3 W
Power Supply Connection	Arbitrary
Electrical Endurance	10000 cycle
Number of Poles	3
Operating Characteristic	Instantaneous (APR High Immunity)
Connecting Capacity	Rigid 16 ... 16 mm ² Flexible 16 ... 16 mm ²
Rated Cross-Section	1 - Solid-Core 16...16 mm ² 4 - Multi-Wired 16...16 mm ²

Environmental

Ambient Temperature	-25...55 °C
Ambient Air Temperature	Operation -25...55 °C
Degree of Protection	IP2X
RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	Refer to RoHS

Technical UL/CSA

Short-Circuit Current Rating (SCCR)	0.03 ... 0.03 A
-------------------------------------	-----------------

Dimensions

Product Net Width	87 mm
Product Net Height	93 mm
Product Net Depth / Length	76 mm
Product Net Weight	0.158 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	118 mm
Package Level 1 Height	80 mm
Package Level 1 Depth / Length	104 mm
Package Level 1 Gross Weight	0.199 kg
Package Level 1 EAN	8012542750338

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030
Country of Origin	Italy (IT)
Selling Unit of Measure	piece

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	9AKK106713A5614
Environmental Information	Refer to RoHS
Instructions and Manuals	2CSB423001D003
RoHS Information	2CSC427001K2701

Popular Downloads	
Data Sheet, Technical Information	9AKK107991A8329
Instructions and Manuals	2CSB423001D003

Classifications	
ETIM 6	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 7	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 8	EC002297 - Residual current circuit breaker (RCCB) module
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85363030
Object Classification Code	F

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Devices RCD Blocks

