

PRODUCT-DETAILS

E 9F14 GG2 KR

E 9F14 GG2 KR Fuse link



General Information

Extended Product Type	E 9F14 GG2 KR
Product ID	2CSM218432R1801
EAN	8012542184324
Catalog Description	E 9F14 GG2 KR Fuse link
Long Description	E 9F14 GG2 is a 14x51 mm cylindrical fuse for circuits protection

Technical

Product Name	Fuse link
Rated Voltage (U_r)	690...690 V
Voltage Range	690 V AC
Rated Current (I_n)	2 A
Rated Primary Current (I_{pn})	2 A
Maximum Breaking Capacity	120 kA
Power Loss	at Rated Operating Conditions per Pole 0.75 W
Utilization Category	gL/gG (Cable protection/equipment protection)
Fuse Type	gG
Release Type	Other

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Dimensions

Product Net Width	0.001 m
Product Net Height	0.051 m
Product Net Depth / Length	0.001 m
Product Net Weight	0.006 kg
Dimensions	14 mm x 51 mm
Size	14x51 mm

Container Information

Package Level 1 Units	10 piece
Package Level 1 Width	0.03 m
Package Level 1 Height	0.07 m
Package Level 1 Depth / Length	0.051 m
Package Level 1 Gross Weight	0.19 kg
Package Level 1 EAN	8012542775232

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	85361010
Country of Origin	Mexico (MX)
Selling Unit of Measure	piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CSC444004D2701
Instructions and Manuals	No document needed
RoHS Information	2CSC444012K2701

Popular Downloads

Data Sheet, Technical Information	2CSC444002B0204
Instructions and Manuals	No document needed

Classifications

ETIM 6	EC002704 - Cylindrical fuse
ETIM 7	EC002704 - Cylindrical fuse
ETIM 8	EC002704 - Cylindrical fuse
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85361010
Object Classification Code	F

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Protection and Safety Devices → Cylindrical and D0 Fuses

