

PRODUCT-DETAILS

E 9F10 GG32 KR

E 9F10 GG32 KR Fuse link



General Information

Extended Product Type	E 9F10 GG32 KR
Product ID	2CSM226302R1801
EAN	8012542263029
Catalog Description	E 9F10 GG32 KR Fuse link
Long Description	E 9F10 GG32 is a 10,3x38 mm cylindrical fuse for circuit protection

Technical

Product Name	Fuse link
Rated Voltage (U_r)	500...500 V
Voltage Range	400 V AC
Rated Current (I_n)	32 A
Rated Primary Current (I_{pn})	32 A
Maximum Breaking Capacity	120 kA
Power Loss	at Rated Operating Conditions per Pole 2.8 W
Utilization Category	gL/gG (Cable protection/equipment protection)
Fuse Type	gG
Release Type	Other

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Dimensions

Product Net Width	0.001 m
Product Net Height	0.004 m
Product Net Depth / Length	0.001 m
Product Net Weight	0.007 kg
Dimensions	10.3 mm x 38 mm
Size	10x38 mm

Container Information

Package Level 1 Units	10 piece
Package Level 1 Width	0.052 m
Package Level 1 Height	0.021 m
Package Level 1 Depth / Length	0.038 m
Package Level 1 Gross Weight	0.075 kg
Package Level 1 EAN	8012542587132

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	85361010
Country of Origin	Mexico (MX)
Selling Unit of Measure	piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	No declaration needed
Instructions and Manuals	No document needed
RoHS Information	2CSC444012K2701

Popular Downloads

Data Sheet, Technical Information	2CSC444002B0204
Instructions and Manuals	No document needed

Classifications

ETIM 6	EC002704 - Cylindrical fuse
ETIM 7	EC002704 - Cylindrical fuse
ETIM 8	EC002704 - Cylindrical fuse
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85361010
Object Classification Code	F

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Protection and Safety Devices → Cylindrical and D0 Fuses

