

## PRODUCT-DETAILS

# E 92/32s PV

## E 92/32s PV Fuse disconnecter



### General Information

|                       |                                                                                                                        |
|-----------------------|------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | E 92/32s PV                                                                                                            |
| Product ID            | 2CSM256913R1801                                                                                                        |
| EAN                   | 8012542569138                                                                                                          |
| Catalog Description   | E 92/32s PV Fuse disconnecter                                                                                          |
| Long Description      | E 92/32s PV is a fuseholder for overcurrent and short circuit protection in PV applications with blown fuse indicator. |

### Technical

|                                    |                                                                                       |
|------------------------------------|---------------------------------------------------------------------------------------|
| Product Name                       | Fuse disconnecter                                                                     |
| Rated Voltage ( $U_r$ )            | 1000 V                                                                                |
| Rated Operational Voltage          | 1000 V DC                                                                             |
| Voltage Range                      | 1000 V DC                                                                             |
| Rated Current ( $I_n$ )            | 32 A                                                                                  |
| Rated Primary Current ( $I_{pn}$ ) | 32 A                                                                                  |
| Power Loss                         | at Rated Operating Conditions per Pole 3 W                                            |
| Number of Poles                    | 2                                                                                     |
| Number of Protected Poles          | 2                                                                                     |
| Utilization Category               | Connecting and disconnecting under no-load conditions - occasional actuation (DC-20B) |
| Mounting Type                      | DIN rail                                                                              |
| Options Provided                   | With LED                                                                              |

|           |          |
|-----------|----------|
| Fuse Size | 10x38 mm |
|-----------|----------|

## Environmental

|                           |                                   |
|---------------------------|-----------------------------------|
| Degree of Protection      | IP20                              |
| RoHS Status               | Following EU Directive 2011/65/EU |
| Environmental Information | See RoHS Information              |

## Dimensions

|                                     |          |
|-------------------------------------|----------|
| Width in Number of Modular Spacings | 2        |
| Product Net Width                   | 0.018 m  |
| Product Net Height                  | 0.085 m  |
| Product Net Depth / Length          | 0.064 m  |
| Product Net Weight                  | 0.062 kg |
| Dimensions                          | 2 module |
| Built-In Depth (t <sub>2</sub> )    | 64 mm    |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 3 piece       |
| Package Level 1 Width          | 0.105 m       |
| Package Level 1 Height         | 0.085 m       |
| Package Level 1 Depth / Length | 0.064 m       |
| Package Level 1 Gross Weight   | 0.375 kg      |
| Package Level 1 EAN            | 8012542569145 |

## Ordering

|                         |              |
|-------------------------|--------------|
| Minimum Order Quantity  | 1 piece      |
| Customs Tariff Number   | 85361010     |
| Country of Origin       | Romania (RO) |
| Selling Unit of Measure | piece        |

## Certificates and Declarations (Document Number)

|                                |                      |
|--------------------------------|----------------------|
| Declaration of Conformity - CE | 2CSC444003D2701      |
| Environmental Information      | See RoHS Information |
| Instructions and Manuals       | No document needed   |
| RoHS Information               | 2CSC444011K2701      |

## Popular Downloads

|                                   |                    |
|-----------------------------------|--------------------|
| Data Sheet, Technical Information | 2CSC444002B0204    |
| Instructions and Manuals          | No document needed |

| Classifications            |                                                            |  |
|----------------------------|------------------------------------------------------------|--|
| ETIM 6                     | EC002705 - Holder for cylindrical fuse                     |  |
| ETIM 7                     | EC002705 - Holder for cylindrical fuse                     |  |
| ETIM 8                     | EC002705 - Holder for cylindrical fuse                     |  |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |  |
| WEEE B2C / B2B             | Business To Consumer                                       |  |
| CN8                        | 85361010                                                   |  |
| Object Classification Code | F                                                          |  |

**Categories**

Low Voltage Products and Systems → Modular DIN Rail Products → Protection and Safety Devices → Cylindrical Fuse Holders and Fuse Switch Disconnectors

