

PRODUCT-DETAILS

E 9F22 AM125

E 9F22 AM125 Fuse link



General Information

Extended Product Type	E 9F22 AM125
Product ID	2CSM258363R1801
EAN	8012542583639
Catalog Description	E 9F22 AM125 Fuse link
Long Description	E 9F22 AM125 is a 22x58 mm cylindrical fuse for motors protection

Technical

Product Name	Fuse link
Rated Voltage (U_r)	500...500 V
Rated Operational Voltage	500 V AC
Voltage Range	500 V AC
Rated Current (I_n)	125 A
Rated Primary Current (I_{pn})	125 A
Maximum Breaking Capacity	120 kA
Power Loss	at Rated Operating Conditions per Pole 9.9 W
Utilization Category	aM (Switchgear protection)
Fuse Type	Cylindrical aM
Release Type	Other
Fuse Size	Cylindrical IEC 22x58

Environmental

RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	See RoHS Information

Dimensions

Product Net Width	0.002 m
Product Net Height	0.006 m
Product Net Depth / Length	0.002 m
Product Net Weight	0.048 kg
Dimensions	22x58 mm
Size	22x58 mm

Container Information

Package Level 1 Units	10 piece
Package Level 1 Width	0.045 m
Package Level 1 Height	0.11 m
Package Level 1 Depth / Length	0.06 m
Package Level 1 Gross Weight	0.05 kg
Package Level 1 EAN	8012542583639

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	85361010
Country of Origin	Tunisia (TN)
Selling Unit of Measure	piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CSC444004D2701
Environmental Information	See RoHS Information
Instructions and Manuals	No document needed
RoHS Information	2CSC444012K2701

Popular Downloads

Data Sheet, Technical Information	2CSC444002B0204
Instructions and Manuals	No document needed

Classifications

ETIM 6	EC002704 - Cylindrical fuse
ETIM 7	EC002704 - Cylindrical fuse
ETIM 8	EC002704 - Cylindrical fuse

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85361010
Object Classification Code	F

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Protection and Safety Devices → Cylindrical and D0 Fuses

