

## PRODUCT-DETAILS

# DSH201 C25 AC30 240V

## DSH201 C25 AC30 240V Residual Current Circuit Breaker with Overcurrent Protection



### General Information

|                       |                                                                                                                                                        |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | DSH201 C25 AC30 240V                                                                                                                                   |
| Product ID            | 2CSR255076R1254                                                                                                                                        |
| EAN                   | 8012542229834                                                                                                                                          |
| Catalog Description   | DSH201 C25 AC30 240V Residual Current Circuit Breaker with Overcurrent Protection                                                                      |
| Long Description      | The DSH201 series is a 1P+N RCBO in two-modules width for the protection of end user single-phase circuits against overload and short-circuit currents |

### Technical

|                                                     |                                                              |
|-----------------------------------------------------|--------------------------------------------------------------|
| Standards                                           | IEC 61009-1<br>IEC 61009-2-1                                 |
| Product Name                                        | Residual Current Circuit Breaker with Overcurrent Protection |
| Tripping Characteristic                             | C                                                            |
| Type of Residual Current                            | Type AC                                                      |
| Rated Operational Voltage                           | 240 V AC                                                     |
| Rated Insulation Voltage (U <sub>i</sub> )          | 500 V                                                        |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> ) | 4 kV                                                         |
| Dielectric Test Voltage                             | 2 kV                                                         |
| Input Voltage Type                                  | AC                                                           |
| Rated Current (I <sub>n</sub> )                     | 25 A                                                         |
| Rated Residual Current                              | 30 mA                                                        |

|                                                                              |                                                                                                    |
|------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| Rated Short-Circuit Capacity ( $I_{cn}$ )                                    | 6 kA                                                                                               |
| Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )                  | 7.5 kA                                                                                             |
| Rated Service Short-Circuit Breaking Capacity, in % of $I_{cu}$ ( $I_{cs}$ ) | 6 kA                                                                                               |
| Leakage Current Type                                                         | AC                                                                                                 |
| Frequency (f)                                                                | 50/60 Hz                                                                                           |
| Rated Frequency (f)                                                          | 50 Hz                                                                                              |
| Power Loss                                                                   | 5.5 W                                                                                              |
| Power Supply Connection                                                      | Arbitrary                                                                                          |
| Energy Limiting Class                                                        | 3                                                                                                  |
| Electrical Endurance                                                         | 10000 cycle<br>20000 cycle                                                                         |
| Number of Poles                                                              | 2                                                                                                  |
| Number of Protected Poles                                                    | 1                                                                                                  |
| Operating Characteristic                                                     | Instantaneous                                                                                      |
| Overvoltage Category                                                         | III                                                                                                |
| Position of Neutral Terminals                                                | Right                                                                                              |
| Earthing Switch Type                                                         | Undelayed                                                                                          |
| Options Provided                                                             | -                                                                                                  |
| Accessories Available                                                        | No                                                                                                 |
| Number of Batteries                                                          | 0                                                                                                  |
| Connecting Capacity                                                          | Busbar 10 mm <sup>2</sup><br>Rigid 25 ... 25 mm <sup>2</sup><br>Flexible 25 ... 25 mm <sup>2</sup> |
| Rated Cross-Section                                                          | 1 - Solid-Core 0.75 ... 25 mm <sup>2</sup><br>4 - Multi-Wired 0.75 ... 16 mm <sup>2</sup>          |

## Environmental

|                         |                                                    |
|-------------------------|----------------------------------------------------|
| Ambient Air Temperature | Operation -25 ... +55 °C<br>Storage -40 ... +70 °C |
| Degree of Protection    | IP20                                               |
| Pollution Degree        | 2                                                  |
| RoHS Status             | Following EU Directive 2011/65/EU                  |

## Technical UL/CSA

|                                     |        |
|-------------------------------------|--------|
| Short-Circuit Current Rating (SCCR) | 0.03 A |
|-------------------------------------|--------|

## Dimensions

|                                     |          |
|-------------------------------------|----------|
| Width in Number of Modular Spacings | 2        |
| Product Net Width                   | 0.035 m  |
| Product Net Height                  | 0.085 m  |
| Product Net Depth / Length          | 0.069 m  |
| Product Net Weight                  | 0.182 kg |
| Built-In Depth ( $t_2$ )            | 35 mm    |

---

**Container Information**

---

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 0.040 m       |
| Package Level 1 Height         | 0.106 m       |
| Package Level 1 Depth / Length | 0.080 m       |
| Package Level 1 Gross Weight   | 0.207 kg      |
| Package Level 1 EAN            | 8012542229834 |

---

---

**Ordering**

---

|                         |            |
|-------------------------|------------|
| Minimum Order Quantity  | 1 piece    |
| Customs Tariff Number   | 85363030   |
| Country of Origin       | Italy (IT) |
| Selling Unit of Measure | piece      |

---

---

**Certificates and Declarations (Document Number)**

---

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 9AKK107492A2001 |
| Instructions and Manuals       | 9AKK1074920470  |
| RoHS Information               | 9AKK107492A2179 |

---

---

**Popular Downloads**

---

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 9AKK107492A7614 |
| Instructions and Manuals          | 9AKK1074920470  |

---

---

**Classifications**

---

|                            |                                                            |
|----------------------------|------------------------------------------------------------|
| ETIM 6                     | EC000905 - Earth leakage circuit breaker                   |
| ETIM 7                     | EC000905 - Earth leakage circuit breaker                   |
| ETIM 8                     | EC000905 - Earth leakage circuit breaker                   |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B             | Business To Consumer                                       |
| CN8                        | 85363030                                                   |
| Object Classification Code | Q                                                          |

---

---

**Categories**

---

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Circuit Breakers with Overcurrent Protection RCBO

