

PRODUCT-DETAILS

ASB 60/100 B/Y

ASB 60/100 B/Y Safety bumper



General Information

Extended Product Type	ASB 60/100 B/Y
Product ID	2TLA076200R0500
EAN	7350024461626
Catalog Description	ASB 60/100 B/Y Safety bumper
Long Description	Bumper ASB, 60 mm wide and 100 mm high, black and yellow. Ordered by meter: order 2,1 m for a 2,1 m long bumper. Length: min 0,15 m and max 3 m. Includes two 5m cables, one at each end of the bumper.

Additional Information

Product Name	Safety bumper
Function	Safety bumper to prevent crushing injuries

Safety Information

Certification Agency	TÜV Nord UR
Safety Category	4
Performance Level (PL)	Up to d

Technical

Overtravel	60 mm
------------	-------

Connection Configuration	Depends on Bumper base price
Color	Black/Yellow
Rated Operational Voltage	24 V DC
Maximum Control Current DC	10 mA
Technical Information	Actuating distance: 15% of bumper height; Maximum compression: 75% of bumper height

Environmental

Degree of Protection	IP54
Ambient Air Temperature	Operation 0 ... +50 °C
Material	Artificial leather

Popular Downloads

Data Sheet, Technical Information	2TLC010001C0202
Instructions and Manuals	2TLC010045M0201

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2TLC172094D0201
Instructions and Manuals	2TLC010045M0201
TÜV Certificate	2TLC010025D0201 2TLC010026D0201

Dimensions

Product Net Width	60 mm
Product Net Depth / Length	1000 mm
Product Net Height	100 mm
Product Net Weight	1.5 kg

Ordering

Minimum Order Quantity	0.15 m
Country of Origin	Germany (DE)
Customs Tariff Number	8536508099

Classifications

Object Classification Code	B
ETIM 7	EC002887 - Pressure sensitive protective device
ETIM 8	EC002887 - Pressure sensitive protective device
eClass	V11.0 : 27273590

Categories

Low Voltage Products and Systems → Control Products → Safety Products → Contact Strips and Bumpers

