

PRODUCT-DETAILS

JSD-HD4-320201

JSD-HD4-320201 Safety Control Devices



General Information

Extended Product Type	JSD-HD4-320201
Product ID	2TLA920065R0000
EAN	4013614499821
Catalog Description	JSD-HD4-320201 Safety Control Devices
Long Description	JSD-HD4-320201 3-pos.enabling device 2 add. switch, spiral cable 1/5m, (PLC, Sentry)

Additional Information

Product Name	Safety Control Devices
Function	Three-position device used to allow a limited movement of the machine when the operator is in the dangerous area.
Sub-Function	1 front and 1 top auxiliary buttons
Status Indicator	No

Safety Information

Performance Level (PL)	Up to e
B10d Value	2 million operations to middle position 968 000 operations to bottom position

Technical

Communication	Contacts
---------------	----------

Interface

Connection Configuration	Spiral Cable Field side: free end
Number of Contacts NO	4
Maximum Switching Current	Main Circuit 20 mA
Maximum Switching Voltage	Main Circuit 30 V
Rated Operational Current DC-12 (I _e)	(24 V) 0.02 A
Rated Operational Voltage	24 V DC

Environmental

Degree of Protection	IP65
Ambient Air Temperature	Operation -10 ... +50 °C
Material	Rubber: NBR; Handle: Polyamid and Noryl

Dimensions

Product Net Width	58 mm
Product Net Depth / Length	34 mm
Product Net Height	202 mm
Product Net Weight	0.74 kg

Ordering

Minimum Order Quantity	1 piece
Country of Origin	Germany (DE)
Customs Tariff Number	85365019

Classifications

ETIM 6	EC002571 - Agreement switch
ETIM 7	EC002571 - Agreement switch
eClass	V11.0 : 27371238

Categories

Low Voltage Products and Systems → Control Products → Safety Products → Safety Control Devices → JSHD

