

PRODUCT-DETAILS

JSD-HD4-010151

JSD-HD4-010151 Safety Control Devices



General Information

Extended Product Type	JSD-HD4-010151
Product ID	2TLA920128R0000
EAN	4013614499906
Catalog Description	JSD-HD4-010151 Safety Control Devices
Long Description	JSD-HD4-010151 3-pos.enabling device w/o add.switch, spiral cable 0,5/2,5m 6-pol. Harting male connector (PLC, Sentry)

Additional Information

Product Name	Safety Control Devices
Function	Three-position device used to allow a limited movement of the machine when the operator is in the dangerous area.
Status Indicator	Yes

Safety Information

Performance Level (PL)	Up to e
B10d Value	2 million operations to middle position 968 000 operations to bottom position

Technical

Communication Interface	Contacts
-------------------------	----------

Connection Configuration	Spiral Cable Harting Connector
Number of Contacts CO	1
Number of Contacts NO	1
Maximum Switching Current	Main Circuit 20 mA
Maximum Switching Voltage	Main Circuit 30 V
Rated Operational Current DC-12 (I_e)	(24 V) 0.02 A
Rated Operational Voltage	24 V DC

Environmental

Degree of Protection	IP65
Ambient Air Temperature	Operation -10 ... +50 °C
Material	Rubber: NBR; Handle: Polyamid and Nory

Dimensions

Product Net Width	58 mm
Product Net Depth / Length	162 mm
Product Net Height	34 mm
Product Net Weight	0.56 kg

Ordering

Minimum Order Quantity	1 piece
Country of Origin	Germany (DE)
Customs Tariff Number	85365080

Classifications

ETIM 6	EC002571 - Agreement switch
ETIM 7	EC002571 - Agreement switch
eClass	V11.0 : 27371238

Categories

Low Voltage Products and Systems → Control Products → Safety Products → Safety Control Devices → JSHD

