



PRODUCT-DETAILS

3BDH000366R0001

TK 701F Diagnostic Cable Sub-D/Sub-D 5 m

General Information

Product ID	3BDH000366R0001
ABB Type Designation	TK 701F
Catalog Description	TK 701F Diagnostic Cable Sub-D/Sub-D 5 m
Long Description	TK 701F, Diagnostic Serial Cable, Sub-D/Sub-D, 5 m

Additional Information

Medium Description	Used to connect a 9-pin serial COM interface of a PC with the DIAG serial interface (COM2) of the PM 783F CPU module.
Technical Information	Connect a 9-pin serial COM interface of a PC with the DIAG serial interface (COM2) of the PM 783F CPU module.
Product Type	Prefabricated_Cable

Ordering

Country of Origin	Germany (DE) United States (US)
HS Code	854442-- Insulated (including enamelled or anodised) wire, cable (including co-axial cable) and other insulated electric conductors, whether or not fitted with connectors; optical fibre cables, made up of individually sheathed fibres, whether or not assembled with electric conductors or fitted with connectors.- Other electric conductors, for a voltage not exceeding 1,000 V :-- Fitted with connectors
Customs Tariff Number	85444290

Dimensions

Product Net Height	50 mm
Product Net Width	40 mm
Product Net Weight	0.35 kg
Cable Length	5 m

Environmental

RoHS Status	Not RoHS Compliant
WEEE Category	Product Not in WEEE Scope

Categories

Control System Products → Control & Communication → Freelance Rack CPUs → Freelance Rack CPUs - Accessories → TK 701F
Diagnostic Cable Sub-D/Sub-D 5 m

Control Systems → Freelance → Controllers → AC 700F → Prefabricated Cables