


PRODUCT-DETAILS

3GAA061311-CSF

No Description Available



General Information

Product ID	3GAA061311-CSF
ABB Type Designation	M3AA 63A 2
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3AA 63A 2
Bearing	6201-2Z/C3
Bearing NDE	6201-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85015100

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.18 kW	2790 r/min	0.51 A	0.750	60.40 %	0.61 N·m	4.50
D	--	50 Hz	230 V	0.18 kW	2790 r/min	0.88 A	0.750	60.40 %	0.61 N·m	4.50
Y	--	60 Hz	460 V	0.18 kW	3420 r/min	0.46 A	0.700	64.00 %	0.50 N·m	5.30

Gross Weight	6.7 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 60.4 %

	Partial Load (75%) 57.8 % Partial Load (50%) 49.5 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 64.0 % Partial Load (75%) 60.2 % Partial Load (50%) 51.4 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor Product ID	3GAA061311-BSF
Product Name	3-Phase squirrel cage motor
Product Net Weight	3.7 kg
Product Type	3AA2__M3AA_IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA061001-CSC 3GAA061311-CSC 3GAA061001-CSE 3GAA061311-CSE
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany Sant Quirze del Vallés - BCN, Spain Vittuone, Italy
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	S

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

