


PRODUCT-DETAILS

3GAA061312-JSF

No Description Available



General Information

Product ID	3GAA061312-JSF
ABB Type Designation	M3AA 63B 2
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3AA 63B 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6201-2Z/C3
Bearing NDE	6201-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85015100

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.25 kW	2790 r/min	0.66 A	0.760	64.80 %	0.86 N-m	4.80
D	--	50 Hz	230 V	0.25 kW	2790 r/min	1.14 A	0.760	64.80 %	0.86 N-m	4.80
Y	--	60 Hz	460 V	0.25 kW	3420 r/min	0.59 A	0.710	68.00 %	0.69 N-m	5.70

Gross Weight	5.1 kg
IC Class	IC411

IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 64.8 % Partial Load (75%) 63.2 % Partial Load (50%) 56.7 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 68.0 % Partial Load (75%) 65.4 % Partial Load (50%) 57.8 %
IM Class	IMB34 IM2101
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor Product ID	3GAA061312-ASF
Product Name	3-Phase squirrel cage motor
Product Net Weight	4.1 kg
Product Type	3AA2__M3AA_IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA061002-JSC 3GAA061002-JSE
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

