


PRODUCT-DETAILS

3GAA062312-CDF

No Description Available



General Information

Product ID	3GAA062312-CDF
ABB Type Designation	M3AA 63B 4
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3AA 63B 4
Bearing	6201-2Z/C3
Bearing NDE	6201-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85015100

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	0.18 kW	1380 r/min	0.34 A	0.680	65.90 %	1.25 N·m	3.60
D	--	50 Hz	400 V	0.18 kW	1380 r/min	0.58 A	0.680	65.90 %	1.25 N·m	3.60
D	--	60 Hz	460 V	0.18 kW	1700 r/min	0.53 A	0.620	69.70 %	1.00 N·m	3.50

Gross Weight	5.4 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 65.9 %

	Partial Load (75%) 64.1 % Partial Load (50%) 57.4 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 69.7 % Partial Load (75%) 67.3 % Partial Load (50%) 60.0 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor Product ID	3GAA062312-BDF
Product Name	3-Phase squirrel cage motor
Product Net Weight	4.4 kg
Product Type	3AA2__M3AA_IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA062312-CBC 3GAA062002-CDE 3GAA062002-CDC
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	D

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

