


PRODUCT-DETAILS

3GAA072001-BRE

M2AA71A4 0,25kWV220D/380Y60Hz

B5+002+209



General Information

Product ID	3GAA072001-BRE
ABB Type Designation	M2AA 71A 4
Catalog Description	M2AA71A4 0,25kWV220D/380Y60Hz B5+002+209

Additional Information

ABB Type Designation	M2AA 71A 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6203-2Z/C3 WT
Bearing NDE	6202-2Z/C3 WT
Country of Origin	Romania (RO)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor
D	--	60 Hz	220 V	0.25 kW	1710 r/min	1.60 A	0.650
Y	--	60 Hz	380 V	0.25 kW	1710 r/min	0.90 A	0.650

Gross Weight	7.2 kg
IC Class	IC411
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF

Invoice Description	M2AA71A4 0,25kWV220D/380Y60Hz B5+002+209
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	7 kg
Product Type	2AA2_M2AA_IE2_AA
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	R
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Aluminum Motors

