

PRODUCT-DETAILS

3GAA081213-BSE053

M2AA 80C 2



General Information

Product ID	3GAA081213-BSE053
ABB Type Designation	M2AA 80C 2
Catalog Description	M2AA 80C 2

Additional Information

ABB Type Designation	M2AA 80C 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6204-2Z/C3
Bearing NDE	6203-2Z/C3
Country of Origin	Finland (FI) China (CN)
Customs Tariff Number	85015220

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	1.10 kW	2875 r/min	2.40 A	0.800	80.60 %	3.60 N·m	7.80
D	--	50 Hz	230 V	1.10 kW	2870 r/min	4.10 A	0.800	80.60 %	3.60 N·m	7.80
Y	--	60 Hz	460 V	1.10 kW	3490 r/min	2.10 A	0.780	82.60 %	3.00 N·m	9.10

Gross Weight	14 kg
--------------	-------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 80.6 % Partial Load (75%) 80.4 % Partial Load (50%) 77.9 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 82.6 % Partial Load (75%) 81.9 % Partial Load (50%) 78.7 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2AA 80C 2
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Moment of Inertia	0.00120 kg/m³
Number of Poles (High)	2
Package Level 1 Units	0 carton
Pre Modified Motor	3GAA081213-BSE
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	11 kg
Product Type	2AA2__M2AA__IE2_AA
Quote Only	No
Selling Unit of Measure	piece
Sound dB (A)	60 dB(A)
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Aluminum Motors



