

PRODUCT-DETAILS

3GAA102530-HFE

M3AA 100LC 4



General Information

Product ID	3GAA102530-HFE
ABB Type Designation	M3AA 100LC 4
Catalog Description	M3AA 100LC 4

Additional Information

ABB Type Designation	M3AA 100LC 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6306-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	500 V	2.20 kW	1450 r/min	3.70 A	0.790	86.40 %	14.40 N-m	7.30
Y	--	60 Hz	575 V	2.20 kW	1760 r/min	3.30 A	0.750	87.60 %	11.90 N-m	9.10

Gross Weight	30 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 86.4 %

	Partial Load (75%) 86.2 %
	Partial Load (50%) 84.1 %
IE Class Data (60 Hz)	IE Class IE2
	Full Load (100%) 87.6 %
	Partial Load (75%) 87.0 %
	Partial Load (50%) 84.3 %
IM Class	IMB35 IM2001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 100LC 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GAA102530-AFE
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	25 kg
Product Type	3AA2_M3AA_IE2_AA
Quote Only	No
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Temperature Class	--
Default	
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	F
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Aluminum Motors
Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors



