

PRODUCT-DETAILS

3GAA103530-HSE

M3AA 100LC 6



General Information

Product ID	3GAA103530-HSE
ABB Type Designation	M3AA 100LC 6
Catalog Description	M3AA 100LC 6

Additional Information

ABB Type Designation	M3AA 100LC 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6306-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Finland (FI) China (CN)
Customs Tariff Number	85015220

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	1.50 kW	945 r/min	3.60 A	0.730	80.30 %	15.10 N-m	3.90
D	--	50 Hz	230 V	1.50 kW	945 r/min	6.26 A	0.730	80.30 %	15.10 N-m	3.90
Y	--	60 Hz	460 V	1.50 kW	1150 r/min	3.20 A	0.700	83.30 %	12.40 N-m	4.40

Gross Weight	31 kg
IC Class	IC411

IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 80.3 % Partial Load (75%) 81.4 % Partial Load (50%) 80.3 %
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 83.3 % Partial Load (75%) 83.3 % Partial Load (50%) 81.4 %
IM Class	IMB35 IM2001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 100LC 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor Product ID	3GAA103530-ASE
Product Name	3-Phase squirrel cage motor
Product Net Weight	26 kg
Product Type	3AA2__M3AA_IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA103442-HSE
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Shanghai, China
Temperature Class Default	--
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Aluminum Motors
Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors



