

PRODUCT-DETAILS

3GAA104001-ASE

M3AA 100LA 8



General Information

Product ID	3GAA104001-ASE
ABB Type Designation	M3AA 100LA 8
Catalog Description	M3AA 100LA 8

Additional Information

ABB Type Designation	M3AA 100LA 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6306-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Poland (PL) China (CN) Sweden (SE)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	230 V	0.75 kW	720 r/min	5.50 A	0.470	70.70 %	9.90 N·m	3.90
Y	--	50 Hz	400 V	0.75 kW	720 r/min	3.20 A	0.470	70.70 %	9.90 N·m	3.90
Y	--	60 Hz	460 V	0.75 kW	865 r/min	2.40 A	0.510	74.20 %	8.20 N·m	4.20

Gross Weight	20.65 kg
--------------	----------

IC Class	IC411
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 100LA 8
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	20 kg
Product Type	3AA2__M3AA_IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA104001-ASA
Replacement Product ID (NEW)	3GAA104510-ASE
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Standards	IEC 60034-1
Stocked At (Warehouses)	Shanghai, China
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Legacy IEC Low Voltage Motors → Aluminum Motors

Motors and Generators → IEC Low Voltage AC Motors → Legacy IEC Low Voltage Motors → Global Motors

Motors and Generators → IEC Low Voltage AC Motors → Marine Motors → Marine Process Performance Motors

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors



