


PRODUCT-DETAILS

3GAA111001-EDE

No Description Available



General Information

Product ID	3GAA111001-EDE
ABB Type Designation	M2AA 112 M 2
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M2AA 112 M 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Spain (ES)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Torque
Y	--	50 Hz	660-690 V	4.00 kW	2850 r/min	4.50 A	0.910	13.40 N·m
D	--	50 Hz	380-420 V	4.00 kW	2850 r/min	7.80 A	0.910	13.40 N·m
D	--	60 Hz	440-480 V	4.60 kW	3450 r/min	7.70 A	0.910	12.73 N·m

Gross Weight	25.65 kg
IC Class	IC411
IM Class	IMB5 IM3001

IP Class	IP55
Insulation Class	ICLF
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Package Level 1 Units	1 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	25 kg
Product Type	AA__Aluminium_motor
Quote Only	No
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Brake Motors

Motors and Generators → IEC Low Voltage AC Motors → Legacy IEC Low Voltage Motors → Aluminum Motors

Motors and Generators → IEC Low Voltage AC Motors → Marine Motors → Marine General Performance Motors

