


PRODUCT-DETAILS

3GAA112101-ADET1

M2AA 112M 4



General Information

Product ID	3GAA112101-ADET1
ABB Type Designation	M2AA 112M 4
Catalog Description	M2AA 112M 4

Additional Information

ABB Type Designation	M2AA 112M 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6306-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Spain (ES) Sweden (SE) Romania (RO)
Customs Tariff Number	85015220

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	4.00 kW	1430 r/min	4.70 A	0.830	83.50 %	26.80 N-m	6.10
D	--	50 Hz	400 V	4.00 kW	1430 r/min	8.30 A	0.830	83.50 %	26.80 N-m	6.10
D	--	60 Hz	460 V	4.00 kW	1740 r/min	7.00 A	0.820	86.30 %	22.00 N-m	7.10

Gross Weight	34 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE1 Full Load (100%) 83.5 % Partial Load (75%) 85.1 % Partial Load (50%) 85.0 %
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 86.3 % Partial Load (75%) 87.4 % Partial Load (50%) 86.7 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2AA 112M 4
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor Product ID	3GAA112101-ADE
Product Name	3-Phase squirrel cage motor
Product Net Weight	29 kg
Product Type	2AA1__M2AA_IE1_AA
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Brake Motors

Motors and Generators → IEC Low Voltage AC Motors → Legacy IEC Low Voltage Motors → Aluminum Motors

Motors and Generators → IEC Low Voltage AC Motors → Legacy IEC Low Voltage Motors → Ex Motors

Motors and Generators → IEC Low Voltage AC Motors → Marine Motors → Marine General Performance Motors

