

PRODUCT-DETAILS

3GAA112360-CDE

M3AA 112MF 4



General Information

Product ID	3GAA112360-CDE
ABB Type Designation	M3AA 112MF 4
Catalog Description	M3AA 112MF 4

Additional Information

ABB Type Designation	M3AA 112MF 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6306-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	5.50 kW	1410 r/min	6.80 A	0.810	82.50 %	37.30 N·m	6.20
D	--	50 Hz	400 V	5.50 kW	1410 r/min	11.80 A	0.810	82.50 %	37.30 N·m	6.20
D	--	60 Hz	460 V	5.50 kW	1730 r/min	10.20 A	0.780	86.20 %	30.50 N·m	7.40

Gross Weight	39 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class NA Full Load (100%) 82.5 % Partial Load (75%) 84.0 % Partial Load (50%) 83.4 %
IE Class Data (60 Hz)	IE Class NA Full Load (100%) 86.2 % Partial Load (75%) 87.2 % Partial Load (50%) 86.2 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 112MF 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor Product ID	3GAA112360-BDE
Product Name	3-Phase squirrel cage motor
Product Net Weight	34 kg
Product Type	3AA2__M3AA_IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA112062-CDA 3GAA112102-CDE
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Aluminum Motors

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

