


PRODUCT-DETAILS

3GAA112904-VSA

No Description Available



General Information

Product ID	3GAA112904-VSA
ABB Type Designation	M2AA 112M
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M2AA 112M
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6307-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Sweden (SE)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	tE	IS/IN
Y	--	50 Hz	380-420 V	4.00 kW	1435 r/min	8.90 A	0.800	0.00 %	0.00 N·m	0	0.00
D	--	50 Hz	220-240 V	4.00 kW	1435 r/min	15.40 A	0.800	0.00 %	0.00 N·m	0	0.00
Y	--	60 Hz	440-480 V	4.60 kW	1735 r/min	8.60 A	0.810	0.00 %	0.00 N·m	0	0.00

Gross Weight	31.000 kg
--------------	-----------

IC Class	IC411
IM Class	IMB35 IM2001
IP Class	IP 55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1.000 piece
Moment of Inertia	0.00000 kg/m³
Number of Poles (High)	4
Output Power	4 kW
Product Name	3-Phase squirrel cage motor
Product Net Weight	30.000 kg
Quote Only	No
Selling Unit of Measure	piece
Service Factor	0.00
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Temperature Rise Class	TCLB
Two Speed Motor	No
Type of Duty	S1
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Brake Motors

Motors and Generators → IEC Low Voltage AC Motors → Legacy IEC Low Voltage Motors → Aluminum Motors

