

PRODUCT-DETAILS

3GAA131130-ADJ122

M3AA 132SC 2



General Information

Product ID	3GAA131130-ADJ122
ABB Type Designation	M3AA 132SC 2
Catalog Description	M3AA 132SC 2

Additional Information

ABB Type Designation	M3AA 132SC 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6206-2Z/C3
Country of Origin	China (CN) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	7.50 kW	2898 r/min	7.59 A	0.910	90.50 %	24.70 N·m	8.10
D	--	50 Hz	400 V	7.50 kW	2898 r/min	13.00 A	0.910	90.50 %	24.70 N·m	8.10
D	--	50 Hz	415 V	7.50 kW	2905 r/min	12.50 A	0.910	90.50 %	24.60 N·m	8.70

Gross Weight	68 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 90.5 % Partial Load (75%) 90.9 % Partial Load (50%) 90.4 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 132SC 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GAA131130-ADJ
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	63 kg
Product Type	3AA0__M3AA_AA
Quote Only	No
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany Vittuone, Italy
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors



