

PRODUCT-DETAILS

3GAA131213-BDE053

No Description Available



General Information

Product ID	3GAA131213-BDE053
ABB Type Designation	M2AA 132SC 2
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M2AA 132SC 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6206-2Z/C3
Country of Origin	Finland (FI) China (CN)
Customs Tariff Number	85015220

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	7.50 kW	2915 r/min	7.92 A	0.880	88.50 %	24.50 N-m	7.60
D	--	50 Hz	400 V	7.50 kW	2915 r/min	13.60 A	0.880	88.50 %	24.50 N-m	7.60
D	--	60 Hz	460 V	7.50 kW	3525 r/min	12.00 A	0.890	89.50 %	20.30 N-m	8.70

Gross Weight	61 kg
--------------	-------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 88.5 % Partial Load (75%) 89.2 % Partial Load (50%) 88.6 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 89.5 % Partial Load (75%) 89.2 % Partial Load (50%) 87.6 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor Product ID	3GAA131213-BDE
Product Name	3-Phase squirrel cage motor
Product Net Weight	56 kg
Product Type	2AA2_M2AA_IE2_AA
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Aluminum Motors



