

PRODUCT-DETAILS

3GAA131313-ADECN

M3AA 132 incl. China energy label (+540)



General Information

Product ID	3GAA131313-ADECN
ABB Type Designation	M3AA 132SC 2 +540
Catalog Description	M3AA 132 incl. China energy label (+540)

Additional Information

ABB Type Designation	M3AA 132SC 2 +540
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6206-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Torque	IS/IN
D	--	50 Hz	380 V	7.50 kW	2890 r/min	14.70 A	0.880	24.50 N-m	7.60
Y	--	50 Hz	660 V	7.50 kW	2890 r/min	8.50 A	0.880	24.50 N-m	7.60
D	--	50 Hz	400 V	7.50 kW	2915 r/min	14.00 A	0.870	20.30 N-m	8.70

Gross Weight	57.38 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2

	Full Load (100%) 88.1 % Partial Load (75%) 88.7 % Partial Load (50%) 88.1 %
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 89.2 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 132 incl. China energy label (+540)
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	57.38 kg
Product Type	3AA2_M3AA_IE2_AA
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Shanghai, China
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors



