

PRODUCT-DETAILS

3GAA132310-JDJ436

M3AA 132MA 4



General Information

Product ID	3GAA132310-JDJ436
ABB Type Designation	M3AA 132MA 4
Catalog Description	M3AA 132MA 4

Additional Information

ABB Type Designation	M3AA 132MA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6206-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	7.50 kW	1462 r/min	9.00 A	0.790	90.60 %	48.90 N-m	6.70
D	--	50 Hz	400 V	7.50 kW	1462 r/min	15.60 A	0.790	90.60 %	48.90 N-m	6.70
D	--	50 Hz	415 V	7.50 kW	1464 r/min	15.60 A	0.760	90.60 %	48.80 N-m	7.00

Gross Weight	70 kg
--------------	-------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 90.6 % Partial Load (75%) 90.7 % Partial Load (50%) 89.8 %
IM Class	IMB34 IM2101
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 132MA 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GAA132310-ADJ
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	63 kg
Product Type	3AA0__M3AA_AA
Quote Only	No
Selling Unit of Measure	piece
Temperature Class	--
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

