

PRODUCT-DETAILS

3GAA132320-JDK

M3AA 132MB 4



General Information

Product ID	3GAA132320-JDK
ABB Type Designation	M3AA 132MB 4
Catalog Description	M3AA 132MB 4

Additional Information

ABB Type Designation	M3AA 132MB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6206-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	5.50 kW	1464 r/min	6.60 A	0.780	89.60 %	35.90 N-m	7.00
D	--	50 Hz	400 V	5.50 kW	1464 r/min	11.40 A	0.780	89.60 %	35.87 N-m	7.00
Y	--	50 Hz	660 V	5.50 kW	1458 r/min	6.70 A	0.800	89.60 %	36.01 N-m	6.50
D	--	50 Hz	380 V	5.50 kW	1458 r/min	11.70 A	0.800	89.60 %	36.02 N-m	6.40
D	--	50 Hz	415 V	5.50 kW	1467 r/min	11.30 A	0.750	89.60 %	35.80 N-m	7.40
D	--	60 Hz	460 V	5.50 kW	1769 r/min	10.00 A	0.750	91.70 %	29.68 N-m	8.00

Gross Weight	73 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 89.6 % Partial Load (75%) 89.8 % Partial Load (50%) 88.6 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 91.7 % Partial Load (75%) 91.7 % Partial Load (50%) 90.5 %
IM Class	IMB34 IM2101
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 132MB 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GAA132320-ADK
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	68 kg
Product Type	3AA3__M3AA_IE3_AA
Quote Only	No
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

