


PRODUCT-DETAILS

3GAA133212-ASE

M2AA 132MA 6

For sale but "Obsolete", replaced by



General Information

Product ID	3GAA133212-ASE
ABB Type Designation	M2AA 132MA 6
Catalog Description	M2AA 132MA 6

Additional Information

ABB Type Designation	M2AA 132MA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6206-2Z/C3
Country of Origin	Spain (ES) Sweden (SE) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor
D	--	50 Hz	230 V	4.00 kW	960 r/min	17.30 A	0.680
Y	--	50 Hz	400 V	4.00 kW	960 r/min	10.00 A	0.680
Y	--	60 Hz	460 V	4.00 kW	1165 r/min	8.70 A	0.670

Gross Weight	47.38 kg
IC Class	IC411

IE Class Data (50 Hz)

IE Class IE2
Full Load (100%) 84.9 %
Partial Load (75%) 85.3 %
Partial Load (50%) 83.9 %

IE Class Data (60 Hz)

IE Class IE1
Full Load (100%) 85.4 %

IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2AA 132MA 6
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Package Level 1 Units	1 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	46 kg
Product Type	2AA2__M2AA__IE2_AA
Quote Only	No
Replacement Product ID (NEW)	3GAA133213-ASE
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Aluminum Motors
Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

