

PRODUCT-DETAILS

3GAA161420-BSF

M2AA 160MLB 2



General Information

Product ID	3GAA161420-BSF
ABB Type Designation	M2AA 160MLB 2
Catalog Description	M2AA 160MLB 2

Additional Information

ABB Type Designation	M2AA 160MLB 2
Bearing	6209-2Z/C3
Bearing NDE	6209-2Z/C3
Country of Origin	Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	15.00 kW	2934 r/min	26.40 A	0.890	91.10 %	48.80 N-m	7.00
D	--	50 Hz	230 V	15.00 kW	2934 r/min	46.10 A	0.890	91.10 %	48.80 N-m	7.00
Y	--	50 Hz	415 V	15.00 kW	2940 r/min	25.90 A	0.880	91.30 %	48.80 N-m	7.40
Y	--	60 Hz	460 V	15.00 kW	3544 r/min	22.80 A	0.900	91.40 %	40.40 N-m	8.10

Gross Weight	106 kg
--------------	--------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 91.1 % Partial Load (75%) 90.6 % Partial Load (50%) 90.0 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 91.4 % Partial Load (75%) 91.6 % Partial Load (50%) 90.1 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2AA 160MLB 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	96 kg
Product Type	2AA2__M2AA__IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA161045-BSG
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Aluminum Motors



