

PRODUCT-DETAILS

3GAA161430-ASF

M2AA 160MLC 2



General Information

Product ID	3GAA161430-ASF
ABB Type Designation	M2AA 160MLC 2
Catalog Description	M2AA 160MLC 2

Additional Information

ABB Type Designation	M2AA 160MLC 2
Bearing	6209-2Z/C3
Bearing NDE	6209-2Z/C3
Country of Origin	Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	18.50 kW	2934 r/min	32.90 A	0.890	90.90 %	60.20 N-m	7.30
D	--	50 Hz	230 V	18.50 kW	2934 r/min	57.60 A	0.890	90.90 %	60.20 N-m	7.30
Y	--	50 Hz	415 V	18.50 kW	2940 r/min	32.10 A	0.880	91.10 %	60.20 N-m	7.70
Y	--	60 Hz	460 V	18.50 kW	3545 r/min	28.30 A	0.890	91.50 %	49.80 N-m	8.40

Gross Weight	114 kg
--------------	--------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 90.9 % Partial Load (75%) 90.4 % Partial Load (50%) 89.3 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 91.5 % Partial Load (75%) 91.4 % Partial Load (50%) 89.9 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2AA 160MLC 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	104 kg
Product Type	2AA2__M2AA__IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA161046-ASG
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Aluminum Motors



