

PRODUCT-DETAILS

3GAA161440-ADG

M3AA 160MLD 2



General Information

Product ID	3GAA161440-ADG
ABB Type Designation	M3AA 160MLD 2
Catalog Description	M3AA 160MLD 2

Additional Information

ABB Type Designation	M3AA 160MLD 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6309-2Z/C3
Bearing NDE	6209-2Z/C3
Country of Origin	Finland (FI) China (CN) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	22.00 kW	2933 r/min	22.00 A	0.900	91.70 %	71.60 N·m	8.10
Y	--	50 Hz	690 V	22.00 kW	2933 r/min	22.00 A	0.900	91.70 %	71.60 N·m	8.10
Y	--	50 Hz	690 V	22.00 kW	2933 r/min	22.00 A	0.900	91.70 %	71.60 N·m	8.10
Y	--	50 Hz	690 V	22.00 kW	2933 r/min	22.00 A	0.900	91.70 %	71.60 N·m	8.10
Y	--	50 Hz	690 V	22.00 kW	2933 r/min	22.00 A	0.900	91.70 %	71.60 N·m	8.10
Y	--	50 Hz	690 V	22.00 kW	2933 r/min	22.00 A	0.900	91.70 %	71.60 N·m	8.10
D	--	50 Hz	400 V	22.00 kW	2933 r/min	38.00 A	0.900	91.70 %	71.60 N·m	8.10
D	--	50 Hz	400 V	22.00 kW	2933 r/min	38.00 A	0.900	91.70 %	71.60 N·m	8.10
D	--	50 Hz	400 V	22.00 kW	2933 r/min	38.00 A	0.900	91.70 %	71.60 N·m	8.10
D	--	50 Hz	400 V	22.00 kW	2933 r/min	38.00 A	0.900	91.70 %	71.60 N·m	8.10
D	--	50 Hz	400 V	22.00 kW	2933 r/min	38.00 A	0.900	91.70 %	71.60 N·m	8.10
D	--	50 Hz	400 V	22.00 kW	2933 r/min	38.00 A	0.900	91.70 %	71.60 N·m	8.10
D	--	50 Hz	415 V	22.00 kW	2940 r/min	37.40 A	0.890	91.90 %	71.60 N·m	8.50
D	--	50 Hz	415 V	22.00 kW	2940 r/min	37.40 A	0.890	91.90 %	71.60 N·m	8.50
D	--	50 Hz	415 V	22.00 kW	2940 r/min	37.40 A	0.890	91.90 %	71.60 N·m	8.50
D	--	50 Hz	415 V	22.00 kW	2940 r/min	37.40 A	0.890	91.90 %	71.60 N·m	8.50
D	--	50 Hz	415 V	22.00 kW	2940 r/min	37.40 A	0.890	91.90 %	71.60 N·m	8.50
D	--	50 Hz	415 V	22.00 kW	2940 r/min	37.40 A	0.890	91.90 %	71.60 N·m	8.50
D	--	60 Hz	440 V	22.00 kW	3539 r/min	34.00 A	0.920	92.20 %	59.30 N·m	8.60
D	--	60 Hz	440 V	22.00 kW	3539 r/min	34.00 A	0.920	92.20 %	59.30 N·m	8.60
D	--	60 Hz	440 V	22.00 kW	3539 r/min	34.00 A	0.920	92.20 %	59.30 N·m	8.60
D	--	60 Hz	440 V	22.00 kW	3539 r/min	34.00 A	0.920	92.20 %	59.30 N·m	8.60
D	--	60 Hz	440 V	22.00 kW	3539 r/min	34.00 A	0.920	92.20 %	59.30 N·m	8.60
D	--	60 Hz	440 V	22.00 kW	3539 r/min	34.00 A	0.920	92.20 %	59.30 N·m	8.60
D	--	60 Hz	460 V	22.00 kW	3546 r/min	32.80 A	0.910	92.40 %	59.20 N·m	9.30
D	--	60 Hz	460 V	22.00 kW	3546 r/min	32.80 A	0.910	92.40 %	59.20 N·m	9.30
D	--	60 Hz	460 V	22.00 kW	3546 r/min	32.80 A	0.910	92.40 %	59.20 N·m	9.30
D	--	60 Hz	460 V	22.00 kW	3546 r/min	32.80 A	0.910	92.40 %	59.20 N·m	9.30
D	--	60 Hz	460 V	22.00 kW	3546 r/min	32.80 A	0.910	92.40 %	59.20 N·m	9.30
D	--	60 Hz	460 V	22.00 kW	3546 r/min	32.80 A	0.910	92.40 %	59.20 N·m	9.30

Gross Weight	133 kg
--------------	--------

IC Class	IC411
----------	-------

IE Class Data (50 Hz)

IE Class IE2
 Full Load (100%) 91.7 %
 Partial Load (75%) 92.8 %
 Partial Load (50%) 92.8 %

IE Class Data (60 Hz)

IE Class IE3
 Full Load (100%) 92.2 %
 Partial Load (75%) 92.8 %
 Partial Load (50%) 92.3 %

IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 160MLD 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	123 kg
Product Type	3AA2_M3AA_IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA161064-ADA 3GAA161034-ADG
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors



