

PRODUCT-DETAILS

3GAA162520-BEE

M3AA 160LB 4



General Information

Product ID	3GAA162520-BEE
ABB Type Designation	M3AA 160LB 4
Catalog Description	M3AA 160LB 4

Additional Information

ABB Type Designation	M3AA 160LB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6309-2Z/C3
Bearing NDE	6206-2Z/C3
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	500 V	15.00 kW	1455 r/min	25.10 A	0.770	90.60 %	98.40 N·m	7.10
D	--	60 Hz	575 V	17.50 kW	1751 r/min	24.70 A	0.780	91.20 %	95.40 N·m	7.20

Gross Weight	94 kg
IC Class	IC411

IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 90.6 % Partial Load (75%) 91.0 % Partial Load (50%) 90.3 %
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 91.2 % Partial Load (75%) 91.7 % Partial Load (50%) 91.4 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 160LB 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	84 kg
Product Type	3AA2__M3AA_IE2_AA
Quote Only	No
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	E
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors



