

PRODUCT-DETAILS

3GAA182410-HDF

M2AA 180MLA 4



General Information

Product ID	3GAA182410-HDF
ABB Type Designation	M2AA 180MLA 4
Catalog Description	M2AA 180MLA 4

Additional Information

ABB Type Designation	M2AA 180MLA 4
Bearing	6210-2Z/C3
Bearing NDE	6209-2Z/C3
Country of Origin	Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	18.50 kW	1464 r/min	20.40 A	0.840	91.20 %	120.00 N·m	7.90
D	--	50 Hz	400 V	18.50 kW	1464 r/min	34.80 A	0.840	91.20 %	120.00 N·m	7.90
D	--	50 Hz	415 V	18.50 kW	1467 r/min	34.30 A	0.820	91.30 %	120.00 N·m	8.40
D	--	60 Hz	460 V	18.50 kW	1770 r/min	30.20 A	0.830	92.40 %	99.80 N·m	9.00

Gross Weight	135 kg
--------------	--------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 91.2 % Partial Load (75%) 92.0 % Partial Load (50%) 91.6 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 92.4 % Partial Load (75%) 92.8 % Partial Load (50%) 91.6 %
IM Class	IMB35 IM2001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2AA 180MLA 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Pre Modified Motor	3GAA182410-ADF
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	125 kg
Product Type	2AA2__M2AA__IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA182043-HDG
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Aluminum Motors



