

PRODUCT-DETAILS

3GAA182420-ADK

M3AA 180MLB 4



General Information

Product ID	3GAA182420-ADK
ABB Type Designation	M3AA 180MLB 4
Catalog Description	M3AA 180MLB 4

Additional Information

ABB Type Designation	M3AA 180MLB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6310-2Z/C3
Bearing NDE	6209-2Z/C3
Country of Origin	Poland (PL) Finland (FI) China (CN)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	22.00 kW	1480 r/min	24.10 A	0.820	93.00 %	141.00 N-m	8.20
D	--	50 Hz	400 V	22.00 kW	1480 r/min	41.50 A	0.820	93.00 %	141.00 N-m	8.20
Y	--	50 Hz	660 V	22.00 kW	1477 r/min	24.60 A	0.840	93.00 %	141.00 N-m	7.50
D	--	50 Hz	380 V	22.00 kW	1477 r/min	42.70 A	0.840	93.00 %	141.00 N-m	7.50
D	--	50 Hz	415 V	22.00 kW	1482 r/min	40.90 A	0.800	93.00 %	141.00 N-m	8.60
D	--	60 Hz	460 V	22.00 kW	1783 r/min	35.80 A	0.820	93.80 %	117.00 N-m	9.30

Gross Weight	186 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 93.0 % Partial Load (75%) 93.7 % Partial Load (50%) 93.5 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 93.8 % Partial Load (75%) 94.2 % Partial Load (50%) 93.7 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 180MLB 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	176 kg
Product Type	3AA3__M3AA_IE3_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA182052-ADK
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany Sant Quirze del Vallés - BCN, Spain
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

