

PRODUCT-DETAILS

3GAA182420-ASF

M2AA 180MLB 4



General Information

Product ID	3GAA182420-ASF
ABB Type Designation	M2AA 180MLB 4
Catalog Description	M2AA 180MLB 4

Additional Information

ABB Type Designation	M2AA 180MLB 4
Bearing	6210-2Z/C3
Bearing NDE	6209-2Z/C3
Country of Origin	Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	22.00 kW	1465 r/min	41.70 A	0.830	91.60 %	143.00 N-m	8.00
D	--	50 Hz	230 V	22.00 kW	1465 r/min	72.50 A	0.830	91.60 %	143.00 N-m	8.00
Y	--	50 Hz	415 V	22.00 kW	1468 r/min	41.30 A	0.810	91.60 %	143.00 N-m	8.40
Y	--	60 Hz	460 V	22.00 kW	1771 r/min	36.20 A	0.820	92.40 %	118.00 N-m	9.00

Gross Weight	147 kg
--------------	--------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 91.6 % Partial Load (75%) 92.2 % Partial Load (50%) 91.8 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 92.4 % Partial Load (75%) 92.6 % Partial Load (50%) 91.3 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2AA 180MLB 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	137 kg
Product Type	2AA2__M2AA__IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA182044-ASG
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Aluminum Motors



