

PRODUCT-DETAILS

3GAA189428-ADG

M3AA 180MLB 2-4



General Information

Product ID	3GAA189428-ADG
ABB Type Designation	M3AA 180MLB 2-4
Catalog Description	M3AA 180MLB 2-4

Additional Information

ABB Type Designation	M3AA 180MLB 2-4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6310-2Z/C3
Bearing NDE	6209-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
YY	--	50 Hz	400 V	24.00 kW	2954 r/min	41.10 A	0.920	91.50 %	78.00 N·m	8.30
D	--	50 Hz	400 V	17.00 kW	1471 r/min	38.30 A	0.720	88.80 %	110.00 N·m	5.80

Gross Weight	187 kg
IC Class	IC411

IE Class Data (50 Hz)	IE Class NA Full Load (100%) 88.8 % Partial Load (75%) 90.0 % Partial Load (50%) 89.5 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 180MLB 2-4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Number of Poles (Low)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	177 kg
Product Type	3AA2__M3AA_IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA188122-ADG
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	Yes
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

