

PRODUCT-DETAILS

3GAA201410-ASG

M3AA 200MLA 2



General Information

Product ID	3GAA201410-ASG
ABB Type Designation	M3AA 200MLA 2
Catalog Description	M3AA 200MLA 2

Additional Information

ABB Type Designation	M3AA 200MLA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312-2Z/C3
Bearing NDE	6210-2Z/C3
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	30.00 kW	2956 r/min	51.60 A	0.900	93.10 %	96.90 N·m	7.70
Y	--	50 Hz	400 V	30.00 kW	2956 r/min	51.60 A	0.900	93.10 %	96.90 N·m	7.70
Y	--	50 Hz	400 V	30.00 kW	2956 r/min	51.60 A	0.900	93.10 %	96.90 N·m	7.70
Y	--	50 Hz	400 V	30.00 kW	2956 r/min	51.60 A	0.900	93.10 %	96.90 N·m	7.70
Y	--	50 Hz	400 V	30.00 kW	2956 r/min	51.60 A	0.900	93.10 %	96.90 N·m	7.70
Y	--	50 Hz	400 V	30.00 kW	2956 r/min	51.60 A	0.900	93.10 %	96.90 N·m	7.70
D	--	50 Hz	230 V	30.00 kW	2956 r/min	91.20 A	0.900	93.10 %	96.90 N·m	7.70
D	--	50 Hz	230 V	30.00 kW	2956 r/min	91.20 A	0.900	93.10 %	96.90 N·m	7.70
D	--	50 Hz	230 V	30.00 kW	2956 r/min	91.20 A	0.900	93.10 %	96.90 N·m	7.70
D	--	50 Hz	230 V	30.00 kW	2956 r/min	91.20 A	0.900	93.10 %	96.90 N·m	7.70
D	--	50 Hz	230 V	30.00 kW	2956 r/min	91.20 A	0.900	93.10 %	96.90 N·m	7.70
D	--	50 Hz	230 V	30.00 kW	2956 r/min	91.20 A	0.900	93.10 %	96.90 N·m	7.70
Y	--	50 Hz	415 V	30.00 kW	2960 r/min	49.70 A	0.900	93.20 %	96.90 N·m	8.30
Y	--	50 Hz	415 V	30.00 kW	2960 r/min	49.70 A	0.900	93.20 %	96.90 N·m	8.30
Y	--	50 Hz	415 V	30.00 kW	2960 r/min	49.70 A	0.900	93.20 %	96.90 N·m	8.30
Y	--	50 Hz	415 V	30.00 kW	2960 r/min	49.70 A	0.900	93.20 %	96.90 N·m	8.30
Y	--	50 Hz	415 V	30.00 kW	2960 r/min	49.70 A	0.900	93.20 %	96.90 N·m	8.30
Y	--	50 Hz	415 V	30.00 kW	2960 r/min	49.70 A	0.900	93.20 %	96.90 N·m	8.30
Y	--	60 Hz	440 V	30.00 kW	3557 r/min	47.00 A	0.900	92.80 %	80.50 N·m	7.90
Y	--	60 Hz	440 V	30.00 kW	3557 r/min	47.00 A	0.900	92.80 %	80.50 N·m	7.90
Y	--	60 Hz	440 V	30.00 kW	3557 r/min	47.00 A	0.900	92.80 %	80.50 N·m	7.90
Y	--	60 Hz	440 V	30.00 kW	3557 r/min	47.00 A	0.900	92.80 %	80.50 N·m	7.90
Y	--	60 Hz	440 V	30.00 kW	3557 r/min	47.00 A	0.900	92.80 %	80.50 N·m	7.90
Y	--	60 Hz	440 V	30.00 kW	3557 r/min	47.00 A	0.900	92.80 %	80.50 N·m	7.90
Y	--	60 Hz	460 V	30.00 kW	3562 r/min	44.90 A	0.900	93.10 %	80.40 N·m	8.70
Y	--	60 Hz	460 V	30.00 kW	3562 r/min	44.90 A	0.900	93.10 %	80.40 N·m	8.70
Y	--	60 Hz	460 V	30.00 kW	3562 r/min	44.90 A	0.900	93.10 %	80.40 N·m	8.70
Y	--	60 Hz	460 V	30.00 kW	3562 r/min	44.90 A	0.900	93.10 %	80.40 N·m	8.70
Y	--	60 Hz	460 V	30.00 kW	3562 r/min	44.90 A	0.900	93.10 %	80.40 N·m	8.70
Y	--	60 Hz	460 V	30.00 kW	3562 r/min	44.90 A	0.900	93.10 %	80.40 N·m	8.70

Gross Weight 220 kg

IC Class IC411

IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 93.1 % Partial Load (75%) 93.5 % Partial Load (50%) 92.8 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 92.8 % Partial Load (75%) 92.7 % Partial Load (50%) 91.6 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 200MLA 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	210 kg
Product Type	3AA2__M3AA_IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA201061-ASA 3GAA201035-ASG
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors



