

PRODUCT-DETAILS

# 3GAA201410-HDK

## M3AA 200MLA 2



### General Information

|                      |                |
|----------------------|----------------|
| Product ID           | 3GAA201410-HDK |
| ABB Type Designation | M3AA 200MLA 2  |
| Catalog Description  | M3AA 200MLA 2  |

### Additional Information

|                       |                             |
|-----------------------|-----------------------------|
| ABB Type Designation  | M3AA 200MLA 2               |
| Altitude              | 1000 m                      |
| Ambient Temperature   | 40 °C                       |
| Bearing               | 6312-2Z/C3                  |
| Bearing NDE           | 6210-2Z/C3                  |
| Country of Origin     | Finland (FI)<br>Poland (PL) |
| Customs Tariff Number | 85015230                    |
| Direction of Rotation | Both sides                  |
| Electrical Data       |                             |

| Conn | Temp Class | Freq  | Voltage | Power    | Speed      | Current | Power Factor | Efficiency | Torque    | IS/IN |
|------|------------|-------|---------|----------|------------|---------|--------------|------------|-----------|-------|
| Y    | --         | 50 Hz | 690 V   | 30.00 kW | 2962 r/min | 30.70 A | 0.870        | 93.30 %    | 96.76 N·m | 7.60  |
| D    | --         | 50 Hz | 400 V   | 30.00 kW | 2962 r/min | 53.20 A | 0.870        | 93.30 %    | 96.76 N·m | 7.60  |
| Y    | --         | 50 Hz | 660 V   | 30.00 kW | 2956 r/min | 32.00 A | 0.880        | 93.30 %    | 96.95 N·m | 6.90  |
| D    | --         | 50 Hz | 380 V   | 30.00 kW | 2956 r/min | 55.50 A | 0.880        | 93.30 %    | 96.95 N·m | 6.90  |
| D    | --         | 50 Hz | 415 V   | 30.00 kW | 2965 r/min | 51.80 A | 0.860        | 93.30 %    | 96.66 N·m | 8.20  |
| D    | --         | 60 Hz | 460 V   | 30.00 kW | 3567 r/min | 46.10 A | 0.870        | 92.40 %    | 80.32 N·m | 9.00  |

|                           |                                                                                                   |
|---------------------------|---------------------------------------------------------------------------------------------------|
| Gross Weight              | 235 kg                                                                                            |
| IC Class                  | IC411                                                                                             |
| IE Class Data (50 Hz)     | IE Class IE3<br>Full Load (100%) 93.3 %<br>Partial Load (75%) 93.4 %<br>Partial Load (50%) 92.5 % |
| IE Class Data (60 Hz)     | IE Class IE3<br>Full Load (100%) 92.4 %<br>Partial Load (75%) 92.2 %<br>Partial Load (50%) 91.0 % |
| IM Class                  | IMB35 IM2001                                                                                      |
| IP Class                  | IP55                                                                                              |
| Insulation Class          | ICLF                                                                                              |
| Invoice Description       | M3AA 200MLA 2                                                                                     |
| Made To Order             | No                                                                                                |
| Minimum Order Quantity    | 1 piece                                                                                           |
| Number of Poles (High)    | 2                                                                                                 |
| Order Multiple            | 1 piece                                                                                           |
| Package Level 1 Units     | 0 pallet (lift)                                                                                   |
| Product Name              | 3-Phase squirrel cage motor                                                                       |
| Product Net Weight        | 225 kg                                                                                            |
| Product Type              | 3AA3__M3AA_IE3_AA                                                                                 |
| Quote Only                | No                                                                                                |
| Replaced Product ID (OLD) | 3GAA201051-HDK                                                                                    |
| SCIP                      | 27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)                                                 |
| Selling Unit of Measure   | piece                                                                                             |
| Stocked At (Warehouses)   | Menden, Germany                                                                                   |
| Temperature Class Default | --                                                                                                |
| Terminator Box Location   | D-End top                                                                                         |
| Two Speed Motor           | No                                                                                                |
| Type of Duty              | S1                                                                                                |
| UNSPSC                    | 26101100                                                                                          |
| Voltage Code              | D                                                                                                 |
| WEEE Category             | 4. Large Equipment (Any External Dimension More Than 50 cm)                                       |

## Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

