

PRODUCT-DETAILS

3GAA201410-HDL

M3AA 200MLA 2



General Information

Product ID	3GAA201410-HDL
ABB Type Designation	M3AA 200MLA 2
Catalog Description	M3AA 200MLA 2

Additional Information

ABB Type Designation	M3AA 200MLA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312-2Z/C3
Bearing NDE	6209-2Z/C3
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	30.00 kW	2957 r/min	30.50 A	0.880	93.30 %	96.88 N-m	8.70
D	--	50 Hz	400 V	30.00 kW	2957 r/min	52.70 A	0.880	93.30 %	96.88 N-m	8.70
D	--	50 Hz	415 V	30.00 kW	2960 r/min	52.00 A	0.860	93.30 %	96.78 N-m	9.20
D	--	60 Hz	440 V	30.00 kW	3559 r/min	47.20 A	0.890	93.30 %	80.49 N-m	9.20
D	--	60 Hz	460 V	30.00 kW	3563 r/min	45.70 A	0.880	93.30 %	80.40 N-m	10.00

Gross Weight	181 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 93.3 % Partial Load (75%) 93.9 % Partial Load (50%) 93.6 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 93.3 % Partial Load (75%) 93.5 % Partial Load (50%) 92.9 %
IM Class	IMB35 IM2001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 200MLA 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Pre Modified Motor Product ID	3GAA201410-ADL
Product Name	3-Phase squirrel cage motor
Product Net Weight	171 kg
Product Type	5AA3__M3AA_IE3_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA201051-HDL
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors

