

PRODUCT-DETAILS

3GAA201430-AEG

M3AA 200MLC 2



General Information

Product ID	3GAA201430-AEG
ABB Type Designation	M3AA 200MLC 2
Catalog Description	M3AA 200MLC 2

Additional Information

ABB Type Designation	M3AA 200MLC 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312-2Z/C3
Bearing NDE	6210-2Z/C3
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015290
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	500 V	45.00 kW	2957 r/min	64.20 A	0.880	93.30 %	145.00 N·m	8.10
D	--	60 Hz	575 V	45.00 kW	3563 r/min	55.80 A	0.880	93.40 %	120.00 N·m	9.20

Gross Weight	235 kg
IC Class	IC411

IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 93.3 % Partial Load (75%) 93.8 % Partial Load (50%) 93.2 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 93.4 % Partial Load (75%) 93.3 % Partial Load (50%) 92.2 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 200MLC 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	225 kg
Product Type	3AA2__M3AA_IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA201033-AEG
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors



