

PRODUCT-DETAILS

3GAA202410-BDF

M2AA 200MLA 4



General Information

Product ID	3GAA202410-BDF
ABB Type Designation	M2AA 200MLA 4
Catalog Description	M2AA 200MLA 4

Additional Information

ABB Type Designation	M2AA 200MLA 4
Bearing	6212-2Z/C3
Bearing NDE	6209-2Z/C3
Country of Origin	Spain (ES) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	30.00 kW	1474 r/min	32.80 A	0.830	92.30 %	194.00 N·m	7.30
D	--	50 Hz	400 V	30.00 kW	1474 r/min	56.50 A	0.830	92.30 %	194.00 N·m	7.30
D	--	50 Hz	415 V	30.00 kW	1476 r/min	55.70 A	0.810	92.30 %	194.00 N·m	7.70
D	--	60 Hz	460 V	30.00 kW	1779 r/min	48.60 A	0.830	93.20 %	161.00 N·m	8.30

Gross Weight	198 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE1 Full Load (100%) 92.2 % Partial Load (75%) 93.6 % Partial Load (50%) 93.7 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 93.2 % Partial Load (75%) 93.8 % Partial Load (50%) 93.2 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2AA 200MLA 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	188 kg
Product Type	2AA2__M2AA__IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA202042-BDG 3GAA202061-BDA
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Aluminum Motors



