

PRODUCT-DETAILS

3GAA221210-ASF

M2AA 225SMA 2



General Information

Product ID	3GAA221210-ASF
ABB Type Designation	M2AA 225SMA 2
Catalog Description	M2AA 225SMA 2

Additional Information

ABB Type Designation	M2AA 225SMA 2
Bearing	6213-2Z/C3
Bearing NDE	6210-2Z/C3
Country of Origin	Poland (PL)
Customs Tariff Number	85015290
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	45.00 kW	2960 r/min	79.20 A	0.900	93.00 %	145.00 N-m	8.10
D	--	50 Hz	230 V	45.00 kW	2960 r/min	137.00 A	0.900	93.00 %	145.00 N-m	8.10
Y	--	50 Hz	415 V	45.00 kW	2964 r/min	77.40 A	0.880	93.20 %	145.00 N-m	8.60
Y	--	60 Hz	460 V	45.00 kW	3567 r/min	69.30 A	0.900	93.00 %	120.00 N-m	9.20

Gross Weight	254 kg
--------------	--------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 93.0 % Partial Load (75%) 93.6 % Partial Load (50%) 92.8 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 93.0 % Partial Load (75%) 92.8 % Partial Load (50%) 91.4 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2AA 225SMA 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	244 kg
Product Type	2AA2__M2AA__IE2__AA
Quote Only	No
Replaced Product ID (OLD)	3GAA221042-ASG
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Aluminum Motors



