

PRODUCT-DETAILS

3GAA222051-BDL

M3AA 225MLB 4

For sale but "Obsolete", replaced by



General Information

Product ID	3GAA222051-BDL
ABB Type Designation	M3AA 225MLB 4
Catalog Description	M3AA 225MLB 4

Additional Information

ABB Type Designation	M3AA 225MLB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6313-2Z/C3
Bearing NDE	6210-2Z/C3
Country of Origin	Sweden (SE) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor
D	--	50 Hz	400 V	37.00 kW	1480 r/min	69.30 A	0.820
Y	--	50 Hz	690 V	37.00 kW	1480 r/min	40.20 A	0.820
D	--	50 Hz	415 V	37.00 kW	1482 r/min	68.50 A	0.800

Gross Weight	258 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3

	Full Load (100%) 93.9 % Partial Load (75%) 94.7 % Partial Load (50%) 94.5 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 225MLB 4
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	248 kg
Product Type	5AA3__M3AA_IE3_AA
Quote Only	No
Replacement Product ID (NEW)	3GAA222210-BDL
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Aluminum Motors



